

## BW™ MAX XT II MULTI-GAS DETECTORS

- Reliably monitors up to four hazards, including H<sub>2</sub>S, CO, O<sub>2</sub>, and combustibles
- Straightforward one-button operation
- Robust motorized SmartSample pump for intelligent remote sampling, ideal for confined spaces
- Reliable pump block detection; water and other liquids are prevented from being drawn into the pump
- Calibration is required only two times per year with a simple one-button automatic procedure
- Tamper-proof adjustable options can be customized to suit any application
- Built-in rechargeable lithium battery
- Rugged and durable water resistant design with built-in concussion-proof boot
- Standard data logging and event logging
- Fully compatible with the MicroDock II automatic test and calibration system

HX922



**Honeywell**

Model No.	Mfg. No.	Description	Price/Each
HX922	XT-XWHM-Y-NA	Gas Detector	
HX923	XT-CK-CC	Carrying Case with Foam Insert	
CONFINED SPACE KITS			
HX924	XT-XWHM-Y-NA-CS	Standard Kit Includes: HX922, IR Connectivity Kit, Regulator, Sampling Probe and Calibration Gas	
HX925	XT-CK-DL	Deluxe Kit Includes: IR Connectivity Kit, Regulator, 10'/3 m Hose, Sampling Probe and Auxiliary Filter (Detector and Calibration Gas Sold Separately)	
POWER OPTIONS & SPARES			
HX926	XT-C01-MC5	Five Unit Cradle Charger	
HX905	GA-PA-1-MC5	Five Unit Power Adaptor	
HX906	GA-VPA-1	12-24 VDC Vehicle Power Adaptor	
HX907	GA-PA-3	12-24 VDC Direct-Wire Power Adaptor	

## BW CLIP REAL TIME SINGLE-GAS DETECTORS

- Real-time gas level display with the ability to calibrate the device
- Maintenance-free: no sensor or battery changes necessary
- Offers extended longevity with a field-replaceable battery and sensor
- Compact, lightweight design with one-button operation
- Designed for a range of harsh environments and extreme temperatures
- Hibernation mode with case accessory or IntelliDoX
- Automated self-test of battery, sensor and electronics
- Wide-angle flash, which alerts simultaneously with audible and vibrating alarm
- Automatic logging of the 35 most recent gas events and bump test results
- Compatible with MicroDock II and Fleet Manager II software
- Affordable, with low cost of ownership
- BW recommends performing a bump test prior to each day's use to confirm sensor response and alarm



**Honeywell**

Model No.	Mfg. No.	Hazard	Measuring Range	Default Alarm Setpoints Low	High	Price /Each
BW CLIP REAL TIME 2-YEAR DETECTORS						
HZ270	BWC2R-H	Hydrogen sulfide (H <sub>2</sub> S)	0-100 ppm	10 ppm	20 ppm	
HZ271	BWC2R-H510	Hydrogen sulfide (H <sub>2</sub> S)	0-100 ppm	5 ppm	20 ppm	
HZ273	BWC2R-M	Carbon monoxide (CO)	0-300 ppm	35 ppm	200 ppm	
HZ274	BWC2R-M50200	Carbon monoxide (CO)	0-300 ppm	50 ppm	200 ppm	
HZ275	BWC2R-X	Oxygen (O <sub>2</sub> )	0-25%	19.5% vol.	23.5% vol.	
HZ276	BWC2R-S	Sulfur Dioxide (SO <sub>2</sub> )	0-100 ppm	5 ppm	20 ppm	
HZ277	BWC2R-S24	Sulfur Dioxide (SO <sub>2</sub> )	0-100 ppm	2 ppm	20 ppm	
BW CLIP REAL TIME 3-YEAR DETECTORS						
HZ278	BWC3R-H	Hydrogen sulfide (H <sub>2</sub> S)	0-100 ppm	10 ppm	20 ppm	
HZ279	BWC3R-M	Carbon monoxide (CO)	0-300 ppm	35 ppm	200 ppm	

## BW CLIP 4 MULTI-GAS DETECTORS

- Alarm Setpoints: 5-10 ppm
- Maintenance-free: no sensor or battery changes necessary
- Compact, lightweight design with one-button operation
- Designed for a range of harsh environments and extreme temperatures
- Automated self-test of battery, sensor and electronics
- Wide-angle flash, which alerts simultaneously with audible and vibrating alarm
- Automatic logging of the 70 most recent gas events and bump test results
- IntelliDoX compatible
- Affordable, with low cost of ownership



HZ284

**Honeywell**



HZ285

Model No.	Mfg. No.	Hazard	Colour	Price /Each
HZ284	BWC4-B-N	O <sub>2</sub> , H <sub>2</sub> S, CO/LEL	Black	
HZ285	BWC4-Y-N	O <sub>2</sub> , H <sub>2</sub> S, CO/LEL	Yellow	

## BW CLIP SINGLE-GAS DETECTORS

- Maintenance-free: no sensor or battery changes necessary
- Offers extended longevity with a field-replaceable battery and sensor
- Compact, lightweight design with one-button operation
- Designed for a range of harsh environments and extreme temperatures
- Hibernation mode with case accessory or IntelliDoX
- Automated self-test of battery, sensor and electronics
- Wide-angle flash, which alerts simultaneously with audible and vibrating alarm
- Automatic logging of the 35 most recent gas events and bump test results
- Compatible with MicroDock II and Fleet Manager II software
- Affordable, with low cost of ownership
- BW recommends performing a bump test prior to each day's use to confirm sensor response and alarm
- Note: Monitors do not have a continuous display of the gas concentration, the concentration of the gas will only be displayed when an alarm point is reached



**Honeywell**

Model No.	Mfg. No.	Hazard	Measuring Range	Default Alarm Setpoints Low	High	Price /Each
BW CLIP 2-YEAR DETECTORS						
HZ174	BWC2-H	Hydrogen sulfide (H <sub>2</sub> S)	1-100 ppm	10 ppm	15 ppm	
HZ175	BWC2-H510	Hydrogen sulfide (H <sub>2</sub> S)	1-100 ppm	5 ppm	10 ppm	
HZ176	BWC2-H515	Hydrogen sulfide (H <sub>2</sub> S)	1-100 ppm	5 ppm	15 ppm	
HZ177	BWC2-M	Carbon monoxide (CO)	0-300 ppm	35 ppm	200 ppm	
HZ178	BWC2-M50200	Carbon monoxide (CO)	0-300 ppm	50 ppm	200 ppm	
HZ181	BWC2-X	Oxygen (O <sub>2</sub> )	0-25%	19.5% vol.	23.5% vol.	
HZ179	BWC2-S	Sulfur Dioxide (SO <sub>2</sub> )	0-100 ppm	5 ppm	10 ppm	
HZ180	BWC2-S24	Sulfur Dioxide (SO <sub>2</sub> )	0-100 ppm	2 ppm	4 ppm	
BW CLIP 3-YEAR DETECTORS						
HZ183	BWC3-H	Hydrogen sulfide (H <sub>2</sub> S)	0-100 ppm	10 ppm	15 ppm	
HZ184	BWC3-M	Carbon monoxide (CO)	0-300 ppm	35 ppm	200 ppm	

### ACCESSORIES

Model No.	Mfg. No.	Description	Qty /Pkg	Price /Each
HZ185	CLIPHB-CASE	Hibernation Case for BW Clip	1	
HZ186	CLIPHB-CASE-B50	Hibernation Case for BW Clip	50	